



VENTILATION EOLO

Colour: grey

Temperature range: -10°C +50°C

Features: Plasticized PVC duct with antishock rigid PVC spiral. Perfectly smooth inside, outside corrugated. **Very light and flexible.** Resistant to atmospheric agents and to most chemicals.

APPLICATIONS:

Suction of air, fumes, gas, powders, sawing, dust. Aerating and conditioning plants, wood working plants. Can be manufactured antistatic upon request.

TECHNICAL DATA:

Part Number	Inside Ø	Min. Wall Thickness	Max. Wall Thickness	Weight	Vacuum	Bending Radius	Roll Length	Volume
	mm	mm	mm	g/m	m H2O	mm	m	m ³
EO 01 019.0 000.0	19,1	0,8	2,4	120	4	29	30	0,031
EO 01 020.0 000.0	20	0,8	2,4	125	4	30	30	0,032
EO 01 025.0 000.0	25	1,0	2,5	155	4	38	50	0,072
EO 01 030.0 000.0	30	1,0	2,8	210	3,5	45	50	0,103
EO 01 032.0 000.0	31,8	1,0	2,9	230	3,5	48	50	0,109
EO 01 035.0 000.0	35	1,0	3,0	255	3,5	53	50	0,138
EO 01 038.0 000.0	38,1	1,0	3,2	300	3	57	50	0,165
EO 01 040.0 000.0	40	1,0	3,3	320	3	60	50	0,180
EO 01 045.0 000.0	45	1,0	3,5	400	3	68	50	0,211
EO 01 050.0 000.0	50	1,0	3,9	485	3	75	50	0,267
EO 01 052.0 000.0	50,8	1,0	3,9	485	3	76	50	0,270
EO 01 055.0 000.0	55	1,0	3,9	535	3	83	50	0,302
EO 01 060.0 000.0	60	1,0	4,0	585	3	90	50	0,366
EO 01 063.0 000.0	63,5	1,0	4,0	615	3	95	50	0,385
EO 01 070.0 000.0	70	1,2	4,2	675	3	105	50	0,547
EO 01 076.0 000.0	76,2	1,2	4,3	755	2,5	114	50	0,628
EO 01 080.0 000.0	80	1,2	4,8	870	2,5	120	50	0,663
EO 01 090.0 000.0	90	1,2	5,1	1020	2,5	135	30	0,447
EO 01 100.0 000.0	100	1,2	5,4	1215	2,5	150	30	0,652
EO 01 102.0 000.0	102	1,2	5,4	1240	2,5	153	30	0,663
EO 01 110.0 000.0	110	1,3	5,6	1355	2,5	164	30	0,754
EO 01 120.0 000.0	120	1,3	5,6	1455	2,5	177	30	0,839
EO 01 127.0 000.0	127	1,3	5,6	1550	2,5	186	30	0,908
EO 01 130.0 000.0	130	1,3	5,6	1600	2,5	190	30	0,953
EO 01 140.0 000.0	140	1,3	5,6	1745	2	203	30	1,048
EO 01 150.0 000.0	151,5	1,3	6,1	1940	2	217	20	0,963
EO 01 152.0 000.0	152,4	1,3	6,3	1945	2	219	20	0,970
EO 01 160.0 000.0	160	1,5	6,4	2125	1,5	228	20	1,045
EO 01 180.0 000.0	180	1,5	6,4	2415	1,5	252	20	1,233
EO 01 200.0 000.0	200	1,5	6,6	2615	1,5	275	20	1,439
EO 01 250.0 000.0	250	1,5	7,0	3495	1	328	10	0,948
EO 01 300.0 000.0	300	1,5	7,2	4370	1	375	10	1,453

Please contact our offices for not listed sizes

