



LIGHT ABRASION VULCANO PU ZR

Colour: transparent with coppered spiral

Temperature range: -40°C + 90°C / -40°F + 194°F

Features: ester based PU duct reinforced with a coppered steel spiral. Wall thickness from 0,35 to 0,50mm. Very flexible, and axially compressible (about 5:1) for easy handling and cost effective stocking and transporting. Resistant to abrasion, mineral oils, ageing, ozone and atmospherical agents. Halogen free, conform to RoHS, can be made antistatic in accordance with TRB S 2153 by grounding the spiral.

APPLICATIONS:

woodworking, dedusting, vapours, small industrial cleaning and suction plants. Can be used as protection sleeve. Suction of dry food according to EC Directives*.

**Please contact our offices for more information*

TECHNICAL DATA:

Part number	Inside Ø	Min. wall thickness	Weight	Vacuum	Bending radius	Roll length	Volume
	mm	mm	g/m	mH2O	mm	m	m ³
ZR 01 050.0 000.0	50	0,35	195	0,40	25	20	0,119
ZR 01 060.0 000.0	60	0,35	240	0,40	30	20	0,139
ZR 01 063.0 000.0	63	0,35	250	0,40	32	20	0,152
ZR 01 070.0 000.0	70	0,35	360	0,40	35	20	0,184
ZR 01 076.0 000.0	76	0,35	390	0,40	38	20	0,235
ZR 01 080.0 000.0	80	0,35	410	0,40	40	20	0,256
ZR 01 090.0 000.0	90	0,35	450	0,40	45	20	0,297
ZR 01 100.0 000.0	100	0,40	510	0,30	50	15	0,286
ZR 01 102.0 000.0	102	0,40	520	0,30	51	15	0,291
ZR 01 110.0 000.0	110	0,40	560	0,30	55	15	0,323
ZR 01 120.0 000.0	120	0,40	610	0,25	60	15	0,374
ZR 01 127.0 000.0	127	0,40	640	0,25	64	15	0,408
ZR 01 130.0 000.0	130	0,40	660	0,20	65	15	0,437
ZR 01 140.0 000.0	140	0,40	710	0,20	70	15	0,514
ZR 01 150.0 000.0	150	0,40	760	0,20	75	15	0,548
ZR 01 152.0 000.0	152	0,40	770	0,20	76	15	0,554
ZR 01 160.0 000.0	160	0,45	880	0,15	80	15	0,606
ZR 01 180.0 000.0	180	0,45	990	0,15	90	15	0,760
ZR 01 200.0 000.0	200	0,45	1100	0,10	100	15	0,963
ZR 01 220.0 000.0	220	0,45	1200	0,10	110	10	1,035
ZR 01 250.0 000.0	250	0,50	1300	0,10	125	-	-
ZR 01 279.0 000.0	279	0,50	1450	0,08	140	-	-
ZR 01 300.0 000.0	300	0,50	1550	0,08	150	-	-
ZR 01 350.0 000.0	350	0,50	1820	0,07	175	-	-
ZR 01 400.0 000.0	400	0,50	2070	0,06	200	-	-

